



ARP 560507N 0131225E
AD ELEV 139 FEET
LEGEND See GEN 2.3
Dimensions in m, ELEV in ft

TWY NR	WIDTH	Surface Bearing strength	Day marking		Taxiway lighting	
			Centerline Holding	Edge	Centerline	Stopbar
A	8 m	CONC PCN	CL HLDG	EDGE	RGL	RGL
B	10 m	CONC+ASPH PCN	CL HLDG	EDGE	RGL	RGL
C	8 m	CONC PCN	CL HLDG			
D	10 m	CONC PCN	CL HLDG			
E	10 m	CONC PCN	CL HLDG			
F	10 m	CONC PCN	CL HLDG			
H	8 m	ASPH PCN	CL			
J	4.8 m	ASPH PCN	CL HLDG		RGL	RGL
K	8 m	CONC PCN	CL	EDGE		
Y	8 m	CONC PCN	CL HLDG	EDGE	RGL	RGL

INS Coordinates for Aircraft Stands

APRON Surface Bearing strength	NR	COORD	ELEV
2			
4			
5			

RWY NR	TRUE & MAG BRG	THR PSN Geoid undulation	Bearing strength	THR ELEV and highest ELEV of TDZ of precision APCH RWY	Declared distances				Approach and runway lighting				
					TORA	TODA	ASDA	LDA	APCH	THR TRID TDZ	VASIS (MEHT)	Edge	End
11R	113.90° GEO 111° MAG	560511.48N 0131052.27E GUND 120 ft	PCN 25 R/B/X/T	THR 122 ft	1989	1989	1989	1989		THR Green	APAPI Left/2.86°	1989/60 m White Caution zone 600 m yellow LH	Red
29L	293.90° GEO 291° MAG	560445.44N 0131237.46E GUND 120 ft	PCN 25 R/B/X/T	THR 136.2 ft TDZ 136 ft	1989	1989	1989	1989	Calvert Cat I 750 m L/L/LH	THR Green WBAR	PAPI Left/3.00° (57.4 ft)	1989/60 m White Caution zone 600 m yellow LH	Red
11L	113.00° GEO 110° MAG	560518.69N 0131132.70E GUND 120 ft	PCN 25 R/B/X/T	THR 126 ft	2010	2010	2010	2010					
29R	293.10° GEO 290° MAG	560453.24N 0131319.68E GUND 120 ft	PCN 25 R/B/X/T	THR 139 ft	2010	2010	2010	2010					